







PRODUCT SELECTION GUIDE

APPLICATION	HEATER FAMILY	PRODUCT DESCRIPTION
Potable Water Freeze Protection IN-PIPE	FPS-BT	All FPS-BT products are approved at both 120/240 V for bulk sale with GTCK and GTKB connection kits.
	PREASSEMBLED Cord sets with GFI	GFI-IN-PIPE - 3 W/ft GFI-IN-PIPE PLUS - 5 W/ft GFI-IN-PIPE EXTRA - 8 W/ft
Freeze Protection ON-PIPE & Process Temperature Maintenance	PAC	Pre-assembled cable, self-regulating 6, 9 W/ft @ 40° F. Multi application industrial quality cable cord set. Good for Pipe Tracing and Roof & Gutter De-Icing(10,12W/ft in 32° F water).
	FPP-BA	Freeze Protection for Pipes. Self regulating, 3, 5, 8, 10 W/ft. Bulk sales. Ordinary area. Pipe Tracing only.(-BA version)
	FPS-BT	Freeze Protection Systems, self regulating, 3, 5, 8, 10 W/ft, offered. C1 D2, C1D1 plus corrosive areas and IN-PIPE
	FPS-BA	Freeze Protection Systems, self regulating, 3, 5, 8, 10 W/ft, offered. C1 D2, C1D1.
	SCS-BT	Steam Cleanable Systems, self regulating, high temperature heater (250°F / 375°F), (-BT), 5, 10, 15, 20 W/ft, C1 D2, C1 D1.
	MIC	Mineral Insulated Cable, our staple. Up to 88 W/ft and 600V. Incoloy 825, the noblest of stainless steels. Very high temperature up to 1100°F. C1D2, C1D1.
Hot Water Temperature Maintenance Systems	FPS-BA	Freeze Protection System, self regulating, 3, 5, 8, 10 W/ft
		
Roof & Gutter De-Icing	PAC	Pre Assembled Cord set. PAC 6/10 – 10 W/ft, PAC 9/12 – 12 W/ft
	GRD	Gutters, Roofs & Drains. 12 W/ft, roof tracing only.
	FPS-BT	Multi Application, -BT for corrosive areas.
Floor Warming & Frost Heave Protection	FPS-BA	9 watts (5FPS) or 12 watts (8FPS).
		
Concrete Snow Melt	CSM	Concrete Snow Melt, self regulating, 25 W/ft, 208/240V.
	MIC	Mineral Insulated Cable, up to 600V, Incoloy 825.
	SCS	20 W/ft for stairs, under garage doors.